



# Government Gazette Staatskoerant

REPUBLIC OF SOUTH AFRICA  
REPUBLIEK VAN SUID-AFRIKA

Vol. 518

Pretoria, 8 August  
Augustus 2008

**No. 31321**

*N.B. The Government Printing Works will not be held responsible for the quality of "Hard Copies" or "Electronic Files" submitted for publication purposes*



**AIDS HELPLINE: 0800-0123-22 Prevention is the cure**

---

---

**CONTENTS • INHOUD**

*No.*

*Page  
No.    Gazette  
         No.*

**GENERAL NOTICE**

**Independent Communications Authority of South Africa**

*General Notice*

|     |  |   |       |
|-----|--|---|-------|
| 944 | Electronic Communications Act (36/2005): Amendment to General Notice 929 of 29 July 2008 ..... | 3 | 31321 |
|-----|--|---|-------|

---

---

---

## GENERAL NOTICE

---

### NOTICE 944 OF 2008



### INDEPENDENT COMMUNICATIONS AUTHORITY OF SOUTH AFRICA (ICASA)

**AMENDMENT TO GENERAL NOTICE 926, GOVERNMENT GAZETTE NO 31290 OF 29 JULY 2008 OF ELECTRONIC COMMUNICATIONS ACT (36/2005) REGULATIONS IN RESPECT OF LICENCE EXEMPTIONS IN TERMS OF SECTION 6 OF THE ELECTRONIC COMMUNICATIONS ACT READ WITH SECTION 31 (6) IN RESPECT OF RADIO FREQUENCY SPECTRUM, ECS AND/OR ECNS**

1. The Independent Communications Authority of South Africa hereby gives notice of an amendment to General Notice 926, Government Gazette No 31290 of 29 July 2008.
2. The following amendment is effected:

Replacement of page 16 of General Notice 926 of Government Gazette No 31290 published on 29 July 2008, which is annexed hereto.

**PARIS MASHILE  
CHAIRPERSON  
ICASA**

## Amended Page 16 of Government Gazette No. 31290.

| COLUMN A<br>Frequency Bands<br>K=kHz M=MHz<br>G=GHz | COLUMN B<br>Type of Device   | COLUMN C<br>Maximum Radiated<br>Power or Field<br>Strength Limits &<br>Channel spacing                          | COLUMN D<br>Relevant<br>Standard                  | COLUMN E<br>Additional<br>Requirements |
|---|--|---|---|--|
| 2400 – 2483.5M                                      | Non-specific SRD.  | 10 mW eirp.<br><br>No duty cycle<br>restriction.<br><br>No channel spacing                                      | EN 300 440<br><br>EN 301 489-1,3<br><br>EN 60950  | CEPT/ERC/REC 70-03                     |
| 2400 – 2483.5M                                      | Wideband<br>Wireless Systems.<br><br>WLAN<br><br>Wideband Data<br>Transmission<br>Applications<br>(WBDS).<br><br>Model Control | 100 mW eirp.<br><br>No duty cycle.<br><br>No channel spacing.   | EN 300 328<br><br>EN 301 489-1,17<br><br>EN 60950 | CEPT/ERC/REC 70-03                     |
| 2400 – 2483.5M                                      | FDDA.  | 25 mW eirp.<br><br>No duty cycle<br>restriction.<br><br>No channel spacing.                                     | EN 300 440<br><br>EN 301 489-1,3<br><br>EN 60950  | CEPT/ERC/REC 70-03                     |
| 2400 – 2483.5M                                      | Low Power Video<br>Surveillance.   | 100 mW eirp.<br><br>No duty cycle<br>restriction.<br><br>No channel spacing.                                    | EN 300 440<br><br>EN 301 489-1,3<br><br>EN 60950  | CEPT/ERC/REC 70-03                     |
| 5150 – 5350M  | Wireless Access<br>Systems/ Radio<br>Local Access<br>Network (WAS &<br>RLAN) indoor use<br>only.                               | 200 mW eirp.<br><br>Dynamic Frequency<br>Selection (DFS) &<br>Transmitter Power<br>Control (TPC)<br>obligatory. | EN 301 893<br><br>EN 301 489-1,17<br><br>EN 60950 | ITU-R M.1625                           |
| 5470 – 5725M  | Wireless Access<br>Systems/ Radio<br>Local Access<br>Network (WAS &<br>RLAN) : Indoor<br>and outdoor use                       | 1 W eirp.<br><br>Dynamic Frequency<br>Selection (DFS) &<br>Transmitter Power<br>Control obligatory              | EN 301 893<br><br>EN 301 489-1,17<br><br>EN 60950 | ITU-R M.1625                           |